

Сервер Тринити ER220HDR-M8

1C

Минимальные требования	Количество, шт
Платформа ER225HSR-M8 (2*CPU Intel Xeon 4/5 Scalable, 32*DDR5 ECC RDIMM/LRDIMM, 24*SAS/SATA, 4*2.5" SAS/SATA/NVMe rear, 2*M.2 2280, 8*PCIe 5.0, OCP 3.0, 2U 19")	1
Intel Xeon Gold 5520+ 28C 205W 2.2GHz 52.5Mb	2
32GB DDR5-5600 ECC Reg	8
LSI MegaRAID SAS 9560-8i + LSICVPM05	1
Cable, SFF-8654 x8 - 2*SFF-8654 x4, 1m	1
Cable, SFF-8654 x4 - 4*SATA, 0.75m	1
480 Gb SSD SATA 1DWPД	2
1.92 Tb SSD SAS 1DWPД	6
2-port 10Gbps, SFP+	1
4-port RJ-45 1Gbps OCP3.0	1
Optical Transceiver 10Gb\с SFP+ SR	2
PSU 1600W CRPS AC 80+ Titanium	2
Кабель электропитания (C13-C14) power cord 3x1кв.мм	2
Уровень Standart на три года	1

Сервер Тринити
ER220HDR-M8

1C

Максимальная комплектация	Количество, шт
Платформа ER220HDR-M8 (2*CPU Intel Xeon 4/5 Scalable, 32*DDR5 ECC RDIMM/LRDIMM, 12*3,5"/2,5" SAS/SATA/NVMe, 4*2.5" SAS/SATA/NVMe rear, 2*M.2 2280, 8*PCIe, OCP 3.0, 2U 19")	1
Intel Xeon Gold 5515+ 8C 165W 3.2GHz 22.5Mb	1
32GB DDR5-5600 ECC Reg	4
LSI MegaRAID SAS 9560-8i + LSICVPM05	1
Cable, SFF-8654 x8 - 2*SFF-8654 x4, 1m	1
Cable, SFF-8654 x4 - 4*SATA, 0.75m	1
480 Gb NVME M.2 2280	2
1.92 Tb SSD SAS 1DWPD	4
2-port 10Gbps, SFP+	1
4-port RJ-45 1Gbps OCP3.0	1
Optical Transceiver 10Gb\с SFP+ SR	2
PSU 1600W CRPS AC 80+ Titanium	2
Кабель электропитания (C13-C14) power cord 3x1кв.мм	2
Уровень Standart на три года	1